

# TECHNICAL DATA SHEET

Update of the document : 19/06/2019  
ISO Reference of this document : DON/LS 03.4279.A



## TARGA S1 SRC

LOW SHOE IN GREY PERFORATED SUEDE  
LEATHER SPLIT

### PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 48(13)  
Weight of one pair in size 42 (8): 1300 gr.  
Norm EN ISO 20345-2011  
AET N°0075/007/161/05/19/1693  
EXT 37/06/19

### Upper features

- Upper : suede perforated leather split
- Tongue : suede perforated leather split
- Quarter lining : non woven absorbent fibers
- Vamp lining : synthetic
- Counter : leather board
- Laces : polyamide
- Tongue marking: size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

### Protections

- Toecap : steel (200 joules)
















### Fitting features

- Lasting insole : textile
- Footbed : foam and textile

### Sole features

- Name : SPORTY
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Outsole density : 1
- Outsole color : black
- Slip resistance SRA (flat) : 0,49 ; (heel) : 0,37
- Slip resistance SRB (flat) : 0,29 ; (heel) : 0,19

### Requirements of the norm EN ISO 20345 : 2011

-  Steel toecap  Polycarbonate toecap  Aluminum toecap (200 joules)
-  Steel midsole  Non metallic midsole
-  A Electric resistance – Antistatic shoes.
-  Ci Insulating sole against cold.
-  E Heel energy absorption.
-  Fo Hydrocarbons resistance of the undermine sole.
-  Hi Insulating sole against heat.
-  Hro Heat resistance of the sole.
-  M Metatarsal protection.
-  P Perforation resistance.
-  Wru Water repellent upper.
-  Wr Water repellent junction upper/sole.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :  
SRA (flat)  $\geq 0,32$   
SRA (heel)  $\geq 0,28$   
SRB (flat)  $\geq 0,18$   
SRB (heel)  $\geq 0,13$

### Advantages = End users benefits

- **2,0-2,2mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- **Non woven absorbent fibers lining**, offers greater comfort and hygiene. 100% polyamide, this material is breathable, transferring humidity from the skin to the outside. It is also highly resistant to abrasion.
- **Special toe cap (ABG) : exclusive LEMAITRE toe cap, asymmetric that matches the shape of the foot** for an elegant design and **wide for greater interior volume** and therefore a better comfort
- **SPORTY sole :**
  - ✓ **Non-slip structure** with a studded open for better drainage of fluids
  - ✓ **Dual density polyurethane (PU2D) injected**
  - ✓ **Heel shock absorber and very thick sole at the heel** for better comfort
  - ✓ **Reinforce heel giving a nice curve and unique style**
  - ✓ **Reinforcements of the PU sole** at the front and the back of the shoe for a better protection of the leather and the shoe
  - ✓ **Very flexible sole and does not rise up on the upper providing an excellent breathability and foot comfort**
  - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
  - ✓ **Cold insulation**
  - ✓ **Sportive design**
- **PARABOLIC profile**
  - ✓ **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
  - ✓ **Spring effect** : gives a more dynamic walk
  - ✓ **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking
- **Sporty shape : injection of the PU sole under the foot, enables :**
  - ✓ **Adaptation of the leather to the shape of the foot**
  - ✓ **Higher breathability of the foot**
  - ✓ **Flexibility of the sole**