

# FIJI S3



Standard EN ISO 20345 : 2011



**LEMAITRE**

Safety since 1974



**Protective toe-cap aluminium 200J**

- light, large and ergonomic
- imperceptible to wear

**Sizes 36 to 48**

Ref.FIJIS30GR

## Product Highlights



- **Upper in water-repellent suede microfiber :** lightness, breathability, tearing and abrasion resistant



- **3D Microporous fabric lining, soft and breathable** pleasant feel of freshness, great ventilation of the foot.



- **Tongue with gusset** to limit intrusion of dust and stones.



- **Protective toe-cap:** aluminium.



- **Puncture-resistant midsole:** high tenacity fabric "0" penetration



## Anti-static sole STREET PU2D

- **Wider and flate sole offering great stability for indoor and urban floors.**
- **Shock absorption at the heel** for muscle fatigue prevention and comfort at a highly strained zone.
- **Asymmetric profile 3 mm studs** for reinforced grip
- **Grooves for liquid dispersion** for slip prevention.

## USAGE

- Light industry, logistics, services, distribution, second-fixings



[lemaître-securité.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority

# FIJI S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- Upper material:** water-repellent suede microfiber
- Tongue with gusset:** high tenacity textile
- Lining:** 3D microporous fabric

## VARIANT



FAYE S1P SRC  
FAYES1PGR

## Practical information

Weight of one shoe size 37: 445 g

AET N°ITASLNB21013347

## Characteristics of the sole

- Designation:** STREET
- Material:** polyurethane / polyurethane
- Antistatic sole**
- SRA Adhesion coefficient:**  
forward flat slip: 0,42 (standard  $\geq 0,32$ )  
forward heel slip: 0,40 (standard  $\geq 0,28$ )
- SRB Adhesion coefficient:**  
forward flat slip: 0,30 (standard  $\geq 0,18$ )  
forward heel slip: 0,16 (standard  $\geq 0,13$ )

## Gencods

<b>36</b>	3237154444368	<b>43</b>	3237154444436
<b>37</b>	3237154444375	<b>44</b>	3237154444443
<b>38</b>	3237154444382	<b>45</b>	3237154444450
<b>39</b>	3237154444399	<b>46</b>	3237154444467
<b>40</b>	3237154444405	<b>47</b>	3237154444474
<b>41</b>	3237154444412	<b>48</b>	3237154444481
<b>42</b>	3237154444429		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP		
S1		(A) (E) (Fo)
S1P		
S2		(A) (E) (Fo) (Wru)
S3		

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

A	Anti-static footwear	Ci	Insulation against cold
E	Shock absorption at the heel	Hi	Insulation against heat
Fo	Fuel oil-resistant outsole	Hro	Outsole resistance to hot contact
Wru	Water penetration and water absorption resistant upper	Wr	Water resistant
ESD	Electrostatic discharge	An	Ankle protection

SRA Slip-resistance on ceramic floors with detergent

SRB Slip-resistance on steel floors with glycerol

SRC = + SRB

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)

**LEMAITRE**  
Safety since 1974

DON\_LS 04 TDS 0035  
update: 24/05/22

Member of

