

TECHNICAL DATA SHEET

UPDATEMENT of the document : 03/06/2019
Référence ISO de ce document : DON/LS 03



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com
contact@lemaitre-securite.com



AMPERA WHITE S1 ESD SRC

SANDAL IN WHITE LEATHER GRAINED

PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 48(13)
Weight of one pair in size 42 (8): 1000 gr.
Norm EN ISO 20345 : 2011
AET : N°0075/007/161/05/19/1693
EXT 01/05/19

Upper features

- Upper : white leather grained
- Tongue : white leather grained
- Lining : tridimensionnal textile (3D)
- Vamp lining : synthetic
- Counter : leather board
- Closing : scratch band
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking

Protections

- Toecap : stainless steel (200 joules)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : Sporty
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,46 ; (heel) : 0,43
- Slip resistance SRB (flat) : 0,26 ; (heel) : 0,20

Requirements of the norm EN ISO 20345 :

	Steel toecap		Polycarbonate toecap		Aluminum toecap (200 joules)
	Steel midsole		Non metallic midsole		
A	A Electric resistance – Antistatic shoes.				
Cl	Cl Insulating sole against cold.				
E	E Heel energy absorption.				
Fo	FO Hydrocarbons resistance of the undermine sole.				
Hi	HI Insulating sole against heat.				
Hro	HRO Heat resistance of the sole.				
M	M Metatarsal protection.				
P	P Perforation resistance.				
Wru	WRU Water repellent upper.				
Wr	WR Water repellent junction upper/sole.				



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,16
SRB (heel) = 0,13

Advantages = End users benefits

This model meets the ESD standard

- **2,0-2,2 mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- **Tridimensionnal textile lining**, soft and breathable, offers greater comfort and hygiene. Thanks to its honeycomb structure it allows better breathability for increased comfort. It is also highly resistant to abrasion.
- **Stainless toecap with special design:**
 - ✓ **Exclusive LEMAITRE toecap** : asymmetric (follows the shape of the foot for a elegant design) and dissymmetrical (toecap is shorter on top for added comfort)
 - ✓ **Treated with Epoxy** to avoid oxidation
 - ✓ **Offset of sizes on SPORTY range for a** for a greater inner volume and therefore a better comfort
- **Sporty sole :**
 - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ **Comfort sole** : very thick sole at the heel
 - ✓ **Dual density polyurethane (PU2D)** injected
 - ✓ **Sportive design**
 - ✓ **Reinforcements of the PU sole** at the front and the back of the shoe for a better protection of the leather and the shoe
 - ✓ **Cold insulation**
 - ✓ **Heel shock absorber**
 - ✓ **Non-slip structure** with a studded open for better drainage of fluids
- **Parabolic profile**
 - ✓ **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
 - ✓ **Spring effect** : gives a more dynamic walk
 - ✓ **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking
- **Sporty shape : injection of the PU sole under the foot, enables :**
 - ✓ Higher breathability of the foot
 - ✓ Adaptation of the leather to the shape of the foot
 - ✓ Flexibility of the sole