

# OSTIN S3



Standard EN ISO 20345 : 2011



Sizes 36 to 48

Ref.OSTIS30NR

## Product Highlights



- **Abrasion resistant suede microfiber** flexible and light.



- **3D microporous fabric lining, soft and breathable** pleasant feel of freshness, good ventilation of the foot.

- **Tongue with gusset** to prevent the intrusion of dust inside the shoe.



- **Protective toe-cap:** aluminium



- **Puncture-resistant midsole:** high tenacity fabric "0" penetration



## Anti-static sole STREET PU2D

- **Wider and flatter sole** offering great stability for indoor and urban floors.
- **Shock absorption at the heel** for muscle fatigue prevention and comfort at a highly strained zone.
- **Asymmetric profile 3 mm studs** for reinforced grip
- **Grooves for liquid dispersion** and slipping prevention.

## USAGE

- Light industry
- Logistics
- Services
- Distribution
- Construction



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# OSTIN S3



Standard EN ISO 20345 : 2011

## Characetristics of the upper

- **Upper material:** abrasion resistant suede microfiber and anti-abrasion TPU film at the front.
- **Tongue with gusset:** abrasion resistant textile.
- **Lining:** 3D microporous lining.

## Characetristics of the sole

- **Designation:** STREET
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adherent coefficient:**  
forward flat slip: 0,42 (standard  $\geq 0,32$ )  
forward heel slip: 0,40 (standard  $\geq 0,28$ )
- **SRB Adherent coefficient:**  
forward flat slip: 0,30 (standard  $\geq 0,18$ )  
forward heel slip: 0,16 (standard  $\geq 0,13$ )

## VARIANT



OWEN S3 SRC  
OWENS30NR

## Practical information

Weight of one shoe size 42: 465 g

CERTIFICATION N°ITASLNB21013347

## Packaging

size 36 to 44	size 45 to 48
<b>shoebox</b> 315 x 220 x 125 mm	<b>shoebox</b> 355 x 235 x 125 mm
<b>carton</b> 635 x 445 x 325 mm	<b>carton</b> 660 x 450 x 360 mm
10 shoeboxes per carton	10 shoeboxes per carton

## Gencods

<b>36</b>	3237154443361	<b>43</b>	3237154443439
<b>37</b>	3237154443378	<b>44</b>	3237154443446
<b>38</b>	3237154443385	<b>45</b>	3237154443453
<b>39</b>	3237154443392	<b>46</b>	3237154443460
<b>40</b>	3237154443408	<b>47</b>	3237154443477
<b>41</b>	3237154443415	<b>48</b>	3237154443484
<b>42</b>	3237154443422		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP			
S1			(A) (E) (Fo)
S1P			(A) (E) (Fo)
S2			(A) (E) (Fo) (Wru)
S3			(A) (E) (Fo) (Wru)

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

(A)	Anti-static footwear	(Ci)	Insulation against cold
(E)	Shock absorption at the heel	(Hi)	Insulation against heat
(Fo)	Fuel oil-resistant outsole	(Hro)	Outsole resistance to hot contact
(Wru)	Water penetration and water absorption resistant upper	(Wr)	Water resistant
	Electrostatic discharge	(An)	Ankle protection

**SRA** Slip-resistance on ceramic floors with detergent

**SRB** Slip-resistance on steel floors with glycerol

**SRC** = **SRA** + **SRB**

**Lemaitre Sécurité**  
17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)



Member of  
**SINAMAP**

**DON\_LS 04 TDS 0079**  
update: 21/12/21

