

TECHNICAL DATA SHEET

Update of this document : 06/02/2017
ISO reference : DON/LS 03.4227.A



RIDERBOOT DARK BROWN SBP CI SRC

Boot in water-repellent full grain pull-up leather with sole in PU/Nitrile rubber VIBRAM® ICE&FIRE

PROTECTIONS FOR THIS MODEL



Sizes available from 35 (2) to 49 (13)
Woman's well fitting : 35 (2) – 39 (5)
Weight per size 38 (5) : 1280 gr.
Man's well fitting : 40 (6) – 49 (13)
Weight per size 42 (8) : 1540 gr.
Norm EN ISO 20345 : 2011

Upper features

- Upper : water-repellent full grain pull-up leather
- Lining : three-dimensional textile
- Vamp lining : synthetic
- Backpart : synderm
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking

Protections 0% METAL

- Toecap : HDHC Fiber composite (200 joules)
- Anti-perforation insert : high tenacity composite fabric « zero » penetration (1100 Newtons)

Fitting features

- Lasting insole : high tenacity composite fabric
- Insock : foam and textile

Sole features

- Name : TRAIL
- Material : Polyurethane / Nitrile rubber- VIBRAM®ICE&FIRE
- Comfort sole color : dark grey
- Outsole color : black
- Slip resistance SRA (flat) : 0,46 ; (heel) : 0,45
- Slip resistance SRB (flat) : 0,22 ; (talon) : 0,14

Advantages = End users benefits


All grounds shoe and 100% non-metallic proposed with a man's well fitting and a well fitting adapted to women's feet morphology, it is particularly adapted to civil engineering, road maintenance, networks, green spaces and Outdoor activities.

- **Leather 2,0 mm thickness** for a better mechanical resistance (abrasion, tear, perforation) and durability.
- **Three-dimensional micro-porous textile as lining** : High breathable thanks to its structure that allows better ventilation of sweat. It is flexible and it improves comfort.
- **Anti-perforation insert high tenacity composite fabric « zero » penetration** : ultra-light, ultra-flexible (insensitive to worn), thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- **HDHC (High Durability Fiber Composite) toecap** : non-metallic, non-magnetic, no heat or cold conduction.
- **TRAIL sole – PU / Caoutchouc Nitrile - VIBRAM®ICE&FIRE**
- ✓ **Comfort sole : injected Polyurethane** : weak density for a better drop shot and an anti-fatigue effect.
- ✓ **Outsole : VIBRAM® in Nitrile rubber** :
 - **Exclusive technical sole** developed thanks to the partnership between Lemaitre and VIBRAM®.
 - **Outdoor sole** with an excellent grip, Hi, HRO.
 - **A unique design, with outdoor look for hard climatic conditions (heat and cold).**
 - **Excellent slip resistance.**
 - **High profile heel (15 mm height)** for an improved safety on ladders.

Basics and additional requirements of the norm EN ISO 20345 : 2011




Toecap

 steel  polycarbonate  aluminium  HDHC Fiber composite

-  Antistatic footwear.
-  Penetration resistance.
-  Resistance of the outsole to hot contact.
-  Water penetration and water absorption resistant upper.
-  Energy absorption of seat region.
-  Heat insulation of sole complex.
-  Metatarsal protection.

Anti-perforation insert

 stainless steel  composite (high tenacity fabric)

-  Resistance of the outsole to fuel oil.
-  Cold insulation of sole complex.
-  Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32
SRA (heel) ≥ 0,28
SRB (flat) ≥ 0,18
SRB (heel) ≥ 0,13

 =  + 