



Prod. Ref.	12612-000
Safety cat.	S3 SRC
Range of sizes	38 - 48 (5 - 13)
Weight (sz. 8)	600 g
Shape	B
Width (5 - 6)	10
Width (6,5 - 13)	11

Description: Black/blue water repellent printed leather and breathable textile ankle boot, **DRYTHERM** 100% polyamide fabric lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**

Plus: METAL FREE. EVANIT footbed, made of EVA and nitrile special compound, with high bearing capacity and variable thickness. Thermoformed, anatomic, punched and coated with highly breathable fabric. Antistatic thanks to a specific treatment on the surface and to seams made of conductive yarns. **ANTI TORSION SUPPORT** made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings and/or unwilling torsion. Perfumed sole

Suggested uses: Construction, maintenance, industries

Care and maintenance: Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	Requirement
Complete shoe	Toe cap: non metallic TOP RETURN toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)	mm	15	≥ 14
		5.3.2.4	Compression resistance (clearance after compression)	mm	14,5	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance	N	To 1100 N	≥ 1100
					No Perforation	
	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance			
			- wet	MΩ	12	≥ 0.1
			- dry	MΩ	461	≤ 1000
	Energy absorption system	6.2.4	Shock absorption	J	34	≥ 20
Upper	Black water repellent printed leather thickness 1,6/1,8 mm	5.4.6	Water vapour permeability	mg/cmq h	> 2,6	≥ 0,8
			Permeability coefficient	mg/cmq	> 28,5	> 15
		6.3.1	Water absorption		15%	≤ 30%
			Water penetration		0,0 g	≤ 0,2 g
Vamp	Felt, breathable, colour dark grey	5.5.3	Water vapour permeability	mg/cmq h	> 4,7	≥ 2
lining	Thickness 1,2 mm		Permeability coefficient	mg/cmq	> 40,6	≥ 20
Quarter	DRYTHERM 100% polyamide fabric, antibacterial, breathable, abrasion resistant, colour grey thickness 1,2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 6,5	≥ 2
			Permeability coefficient	mg/cmq	> 53,3	≥ 20
Sole	Antistatic Polyurethane/TPU directly injected in the upper: Outsole: Black TPU, slipping resistant, abrasion resistant and hydrocarbons resistant. Midsole: Grey polyurethane, low density, comfortable and anti-shock.	5.8.3	Abrasion resistance (lost volume)	mm ³	66	≤ 150
		5.8.4	Flexing resistance (cut increase)	mm	2	≤ 4
		5.8.6	Interlayer bond strength	N/mm	3,8	≥ 3
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	1	≤ 12
		5.3.5	SRA : ceramic + detergent solution – flat		0,40	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,31	≥ 0,28
	SRB : steel + glycerol – flat		0,19	≥ 0,18		
	SRB : steel + glycerol – heel (contact angle 7°)		0,16	≥ 0,13		
	Adherence coefficient of the sole					